

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A dryer comprising:
 - a housing;
 - a drum rotatably installed in the housing;
 - a heating apparatus for supplying hot air to the drum;
 - a door opening/closing an entrance formed at the housing for putting a laundry in the drum; and
 - an apparatus for opening/closing the door, comprising:
 - a hook provided at one side of the door of the dryer, the hook having a hanging portion at one end;
 - a latch body provided to the housing in the vicinity of the entrance wherein the hanging portion is inserted the latch body;
 - a pair of holders provided to confront each other in the latch body to hold the hanging portion;
 - a pair of springs provided in rear of the holders, respectively; and
 - a support member provided to the latch body to support each of the springs to move stably.

2. (Original) The dryer as claimed in claim 1, the latch body comprising:
a first reception part receiving the hanging portion; and
a pair of second reception parts provided adjacent to both sides of the first reception part to hold to guide the holders, respectively.

3. (Original) The dryer as claimed in claim 2, wherein a pair of passing holes communicating with the second reception parts are formed at both of the sides of the first reception part to let the holders pass through, respectively.

4. (Original) The dryer as claimed in claim 2, wherein a recess is formed at one end of each of the second reception parts to support the corresponding spring.

5. (Original) The dryer as claimed in claim 2, wherein a hanging protrusion is formed on one side of each of the holders to be held by an upper end of the first reception part.

6. (Original) The dryer as claimed in claim 1, wherein the hanging portion has a triangular cross-section.

7. (Original) The dryer as claimed in claim 6, wherein confronting planes of the holders are inclined to correspond to the triangular cross-section of the hanging portion.

8. (Original) The dryer as claimed in claim 1, wherein a surface of the hanging portion to be brought contact with the holders is rounded.

9. (Original) The dryer as claimed in claim 8, wherein two confronting tips of the holders are rounded.

10. (Original) The dryer as claimed in claim 1, wherein a hollow portion is provided at a rear side of each of the holders to have one end of the corresponding spring inserted therein.

11. (Original) The dryer as claimed in claim 1, further comprising a latch cap covering the first and second reception parts to prevent separation of the holders and the springs.

12. (Original) The dryer as claimed in claim 11, wherein fixing protrusions protrude from a bottom of the latch cap to hold one ends of the springs, respectively.

13. (Original) The dryer as claimed in claim 11, wherein guide protrusions protrude from a bottom of the latch cap to guide to move the holders, respectively.

14. (Original) The dryer as claimed in claim 11, wherein coupling holes are formed at corners of the latch cap and wherein bolts are screwed in the coupling holes, respectively to fix the latch cap to the latch body.

15. (Original) The dryer as claimed in claim 1, wherein the hook is built in one body of a fixing plate screw-coupled to one side of the door.

16. (Original) The dryer as claimed in claim 1, wherein coupling holes are formed at both sides of the latch body and wherein bolts are screwed in the coupling holes, respectively to fix the latch body to the front panel.

17. (Original) The dryer as claimed in claim 1, wherein an insertion hole is formed in the latch body so that the hanging portion is inserted in the insertion hole.

18. (Original) The dryer as claimed in claim 17, wherein the insertion hole comprises an incline surface inclining inward to guide the hanging portion.

19. (Original) The dryer as claimed in claim 1, wherein the support member establishes an installation location of the corresponding spring.

20. (Original) The dryer as claimed in claim 1, wherein the support member forms a receiving part for holding at least a portion of the corresponding spring.

21. (Original) The dryer as claimed in claim 1, wherein the support member prevents the corresponding spring from fluctuating and lifts the corresponding spring to a predetermined height.

22. (Original) The dryer as claimed in claim 1, wherein the support member matches a center of the corresponding spring to that of the corresponding holder.

23. (Original) The dryer as claimed in claim 1, wherein the support member comprises a pair of vertical ribs installed at both lateral sides of the corresponding spring.

24. (Currently Amended) The dryer as claimed in claim 1 ~~or claim 23~~, wherein the support member comprises a horizontal rib installed beneath the corresponding spring.